




EN



### PROTECTIVE SUITS CAT. III



CE III CAT

Single-use protective suit in white non-woven fabric with white external lamination. Single-use protective suit in white non-woven fabric with white external lamination.

Type 4-B/5-B/6-B Category III Personal Protective Equipment: partial protection against liquid chemicals with spray-tight hermetic seals (Type 4); protection against particulate matter in the air (Type 5); limited protection against liquid chemicals (Type 6); protection against the risk of accumulation of static charges; protection against infectious agents (B); protection against radioactive contamination.

#### Composition

55% POLYPROPYLENE + 45% POLYETHYLENE  
Polypropylene with polyethylene laminates.

#### Size

S-M-L-XL-XXL-3XL

#### Weight


63 g/m<sup>2</sup>

#### Colour

WHITE/LIGHT BLUE  
(00035)

#### Packaging (50)

MINIMUM SALE UNIT: 50 pc/box



BOX

Packed in single bags.



CARTON

50-piece box.

Carton weight: 13,7 Kg  
Carton size: 60x40x40 cm









1 COLOUR










## Certifications

This product has been manufactured in compliance with the requirements of Regulation (EU) 2016/425, classified as PPE III cat. and in compliance with the following regulations:

Symbol	Standard
	<b>EN ISO 13688:2013</b> Protective clothing - General requirements.
	<b>EN 1149-5:2018</b> Protective clothing - Electrostatic properties - Part 5: Performance requirements of materials and design against the risk of accumulation of electrostatic charges.
	<b>EN14605:2005+A1:2009</b> Performance requirements for clothing with spray-tight ( <b>Type 4</b> ) connections providing protection (Type 4) against liquid chemical agents: 4% bleach (level 6).
	<p><b>EN 13034:2005 + A1: 2009</b> Protective clothing against liquid chemicals - Performance requirements for chemical protective clothing that offer limited protection against liquid chemicals (<b>Type 6</b>) such as level 3 sodium hydroxide (10%), level 3 sulphuric acid (30%), level 3 o-xylene and level 3 1-butanol.</p> <p><b>EN ISO 13982-1: 2004/A1:2010</b> Protective clothing for use against solid particulates - Part 1: Performance requirements for chemical protective clothing providing protection to the full body against airborne solid particles (<b>type 5</b> clothing) according to EN ISO 13982-2: 2004.</p>
	<b>EN 14126:2003/AC:2004</b> Performance requirements and test methods for protective clothing against infectious agents: ( <b>Type 4-B, Type 5-B, Type 6-B</b> ).
	<b>EN 1073-2:2002</b> Protective clothing against radioactive contamination - Part 2: Requirements and test methods for non-ventilated protective clothing against particulate radioactive contamination: classified as ( <b>level 1</b> )

## Maintenance:

Garment care must take place according to the following:

						
Do not wash	Do not bleach	Do not tumble dry	Do not iron	Do not dry clean	Flammable	Do not reuse, DISPOSABLE/SINGLE-USE

## Sizes

Measurements for each size:

SIZES	CHEST (A) (CM)	HEIGHT (B) (CM)
<b>S</b>	86-94	158-166
<b>M</b>	94-102	166-174
<b>L</b>	102-110	174-182
<b>XL</b>	110-118	182-190
<b>XXL</b>	118-129	190-198
<b>3XL</b>	129-141	198-206

